

Utility Saw Series

Heavy-Duty, Metal-Cutting Utility Band Saws that offer
Fast and Accurate cuts with Portability that's excellent for Onsite Jobs



HEM[®] SAW

— The saw that cuts straight. —

BERGSEN INC. - AUTHORIZED HEM SAW DEALER

Utility Saw Series

These tabletop saws are ideal for smaller jobs. They are impressive in their cutting and speed capabilities, saving up to 60% cutting time compared to traditional band saws. Many of these models do not require lubrication. These saws meet the highest standards for quality and are inspected and tested throughout the manufacturing process.

782XLH

Capacity: 3.9" W x 3.3" H (4.1" Round)

Miter: 2.3" H x 2.5" left @45°

Blade: 1/2" x 52-1/2" x .025"

115V, 2-Speed Motor,
One-Way 45° Miter, Manual Head Tilt, Manual Pull-Down,
Manual Vise, Easy Blade Tensioning,
Adjustable 19.6" Stop, Dry Cutting, Weight: 35 lbs.



Optional Work Table

Allows the 782XLH to be stationed upright to be used for vertical sawing.

(Optional table only works on 782XLH model)

ABS-105

Capacity: 3.9" W x 3.3" H (4.1" Round)

Miter: 2.3" H x 2.5" left @45°

Blade: 1/2" x 52-1/2" x .025"

Semi-Automatic Operation,
115V, 2-Speed Motor, Adjustable Cutting Force,
One-Way 45° Miter, Manual Head Tilt,
Manual Vise, Easy Blade Tensioning,
Adjustable 19.6" Stop, Dry Cutting, Weight: 40 lbs.



NG120XL

Capacity: 4.7" W x 4.0" H (4.7" Round)
Miter: 3.1" H x 3.0" left @45°
Miter: 1.6" H x 1.9" left @ 60°
Blade: 1/2" x 56-3/4" x .025"

NG Reverse Band Rotation, 115V, Variable Speed,
One-Way 60° Miter, Manual Head Tilt, Manual Pull-Down,
Manual Vise, Easy Blade Tensioning w/ Clutch Safety,
Adjustable 19.6" Stop, Dry Cutting, Weight: 39 lbs.

ABS-NG120XL

Capacity: 4.7" W x 4.0" H (4.7" Round)
Miter: 3.1" H x 3.0" left @45°
Miter: 1.6" H x 1.9" left @ 60°
Blade: 1/2" x 56-3/4" x .025"

Semi-Automatic Operation, Adjustable Cutting Force,
NG Reverse Band Rotation, 115V, Variable Speed,
One-Way 60° Miter, Manual Head Tilt,
Manual Vise, Easy Blade Tensioning w/ Clutch Safety,
Adjustable 19.6" Stop, Dry Cutting, Weight: 45 lbs.



*Reverse Blade Rotation Provides 60% faster cutting
over traditional band saws!*

NG160

Capacity: 6.2" W x 5.5" H (5.9" Round)
Miter: 3.9" H x 4.7" left @45°
Blade: 1/2" x 68-1/4" x .025"

NG Reverse Band Rotation, 115V, Variable Speed,
One-Way 45° Miter, Manual Head Tilt, Manual Pull-Down
Manual Vise, Easy Blade Tensioning w/ Clutch Safety,
Adjustable 19.6" Stop, Dry Cutting, Weight: 77 lbs.

ABS-NG160

Capacity: 6.2" W x 5.5" H (5.9" Round)
Miter: 3.9" H x 4.7" left @45°
Blade: 1/2" x 68-1/4" x .025"

Semi-Automatic Operation, Adjustable Cutting Force,
NG Reverse Band Rotation, 115V, Variable Speed,
One-Way 45° Miter, Manual Head Tilt,
Manual Vise, Easy Blade Tensioning w/ Clutch Safety,
Adjustable 19.6" Stop, Dry Cutting, Weight: 85 lbs.



N215XL

Capacity: 7.7" W x 5" H (6.6" Round)
Miter: 4.3" H x 5.9" left @45°
Miter: 2.9" H x 3.9" left @ 60°
Blade: 3/4" x 84-1/4" x .035"

220V Single Phase - 1 Speed Motor,
One-Way 60° Miter, Manual Head Tilt, Manual Pull-Down,
Manual Vise, Easy Blade Tensioning w/ Clutch Safety,
Adjustable 19.6" Stop, Flood Coolant, Emergency Stop,
Weight: 352 lbs., Price Includes Base



Optional Jobby Table

This portable table is excellent for use when cutting with the smaller utility saws.



Replacement Blades

Saw blades are available and in stock for all utility saw models, along with the other replacement parts that are always stocked.



For more information, please contact Authorized HEM Saw Dealer • Bergsen, Inc. • Phone: (562) 236-9787

Band Saws • Material Handling • Metalworking Fluids Custom Applications • Factory Service Department • Fast-Available Parts



Horizontal Pivot



Horizontal Miter



Vertical



Dual Column



Wide Flange



Bergsen, Inc. Authorized HEM Saw Dealer

12241 Florence Ave • Santa Fe Springs, CA • 90670

Phone: (562) 236-9787 Fax: (562) 236-9797

E-Mail: hemsaw@bergsen.com

HEM, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any model, at any time without notice and without incurring any obligations. Dimensions may vary. Please contact HEM, Inc. for a certified dimensional drawing of your specific model. Copyright 112800 HEM, Inc. All rights reserved.